



TOWERS TANKS

Pty Ltd

**FREE CALL
ANYTIME**

1800 65 99 46

WATER

- Tanks include an inlet strainer, an overflow, a brass outlet and ball valve up to 2"

MODEL NUMBER	SIZE LITRES	DIA(mm)	INLET HGT (mm)	APEX HGT (mm)
TT 10000	47,000	4500	3060	3460
TT 8000	35,250	4500	2450	2800
TT 6000	26,000	3800	2700	3000
TT 5000	21,500	3800	2230	2550
TT 4000	18,500	3300	2520	2600
TT 3000	13,750	3300	1980	2000
TT 2400	10,250	2425	2550	2550
TT 1750	8,250	2425	2000	2000
TT 1200	5,250	2425	1400	1400
TT 1100	5,000	1730	2240	2300
TT 1100 Squat	5,000 Squat	2100	1620	1715
TT 1100 Tall	5,000 Tall	1840	2050	2170
TT 1000	4,600	1750	2080	2080
TT 750	3,400	1600	1870	1870
TT 500	2,300	1400	1605	1605
TT 250	1,150	1100	1375	1375
TT 100	500	855	1025	1025
TTS 3000	3,000L Slimline	LEN.2680	WID. 700	HGT 1950
TST 1100 SL	5,000L Slimline	LEN. 2755	WID. 1045	HGT 1980

Standard Tank colours are: Refer to Colour Chart
Molasses : Black Only

Re: Delivery of Large Water Tanks (above 21,500L).
Please ensure that adequate access is available to site for delivery of tanks.
For a Truck and Trailer Combination: 19m long x 3.5m wide x 5m high.

To comply with Workplace Health and Safety requirements, the minimum customer requirements for delivery, if the site is level and accessible are:
500L-- 8,500L : One able-bodied person required onsite at time of delivery.
10,250L - 47,000L : Three able-bodied people required onsite at time of delivery.

A FLEXIBLE COUPLING MUST BE FITTED TO EACH OUTLET TO VALIDATE THE GUARANTEE.

Been 'round for years